

GREASES THAT WORK



XTREME™ Ultra 1000 Calcium Sulfonate Grease #2

Xtreme Ultra 1000 Calcium Sulfonate Grease is a high performance, extreme pressure grease with resistance to corrosive saltwater environments. Xtreme Ultra 1000 Calcium Sulfonate Grease is crafted using calcium sulfonate thickeners that provide outstanding film strength to protect moving surfaces. This product is ideal for automotive use as well as extreme pressure applications in construction, mining, agricultural, logging, hauling, and other industries where a shear-stable, high load carrying, corrosion resistant grease is required.

PREMIUM BASE OILS

We begin with virgin base oils that provide excellent performance and pumpability in cold temperatures, resists oxidation, and retains film thickness as temperatures vary during operation.

FORTIFIED WITH SPECIAL POLYMERS

Our polymer package reduces oil separation and stays in application longer while resisting water washout. This product protects equipment from rust in humid and water ingress conditions.

CALCIUM SULFONATE THICKENERS

By using calcium sulfonate thickeners, Xtreme Ultra 1000 has excellent oxidation stability and inherent EP and anti-wear properties.



| TYPICAL PROPERTIES | ASTM Test Method | Ultra 1000 Calcium Sulfonate Grease Calcium Sulfonate Complex | |
|--|----------------------------|--|--|
| Thickener | | | |
| NLGI Grade | | 2 | |
| Texture | Visual | Smooth, Tacky | |
| Color | | Blue | |
| Dropping Point, °C (°F) | D-2265 | 300 (550) Min. | |
| Penetration • Worked 60 strokes | D-217 | 275 | |
| Water Washout at 79.4°C, % wt | D-1264 | 0.75 | |
| Water Spray-Off, % | D-4049 | WAITING ON DATA FROM TECH | |
| Base Oil Viscosity @ 40°C, cSt | D-445 | 220 | |
| Rust Preventative Properties | D-1743 | PASS | |
| Extreme Pressure Timken, OK Load, LB Four-Ball EP OK Load, kG Four-Ball Wear, Scar Diameter, mm | D-2509 D-2596 D-2266 | 70 620 0.56 | |
| Seal Compatibility | D-4289 | PASS | |
| Wheel Bearing Life, hours | D-3527 | 80 | |
| Fretting Wear, mg | D-4170 | 4.8 | |
| Leakage Tendencies, g | D-4290 | 0.43 | |
| Low Temperature Torque | D-4693 | 5.1 | |
| | | | |

| Part Numbers for Xtreme Ultra 1000 Calcium Sulfonate Grease #2 | | | | | |
|--|--------|--------|--------|--------|--|
| 40/14 oz | 1/35# | 1/120# | 1/400# | Bulk | |
| 503805 | 574602 | 574611 | 574688 | 501778 | |

The information on this Product Data Sheet is believed to be accurate and is typical of current production. Specifications are subject to change without notice. For additional qualifications, please contact your Martin Lubricants Sales Representative. (03/2020)